

Technical Data Sheet

Putzmeister Mixokret M760 Stage V (5.5) "Green Efficiency"

Brand New to the Fleet in 2023, the M 760 Stage V – Green Efficiency conveys screed up to 190 metres** horizontally and 135 metres** vertically.

The keypad with innovative, colour LED display in the control cabinet makes operation incredibly simple and efficient.

Maximum power and efficiency is available with the Deutz diesel engine (emission category Stage V). The integrated diesel particle filter cleans the exhaust gases and protects our environment from pollution.

The Benefits:

- Maximum power – meets all requirements of the current "Stage V" emission category.
- Higher output and more efficient through.
- machine performance management in series.
- Hydraulic mixing unit with overload protection and reverse.
- New robust keypad improves usability.
- Auto-Power-Off – prevents the battery from draining overnight.
- Large diesel tank with 70 litres volume



Technical Data.

Model :	M760 DH	Equipment:
Mixer Drum	260 l, 200 l useful capacity	Auto-Power Off
Delivery rate*	4 m ³ /h	Eye & Pin Coupling
Delivery pressure	8 bar	Central Lubrication System
Delivery range**	190 m horizontally / 135 m vertically (45 storeys)	Discharge Stand
Compressor	4.8 m ³ /min; cut-off pressure 8 bar	Fuel Gauge in display
Engine	Diesel, 3-cylinder Deutz with turbocharging, 44.5 kW (emission category Stage V)	Grease Pump for Lubrication System
Weight	1,715 kg	Lifting Eye
Tank capacity	70 litres	
Length	4,780 mm	
Width	1,480 mm	
Height	1,520 mm	
Filling height	820 mm	
Maximum grain size	16 mm	
Chassis	braked, approved for speeds up to 80 km/h	
Mixing unit	hydraulic with overload protection and reverse	
* The delivery rate is theoretical and depends on the pump pressure. ** The data is based on experience and depends on the material properties. *** All data provided by Putzmeister (Pump Manufacturer)		