

Technical Data Sheet

SP 25 DHF

Robust and powerful – for large volumes of self-levelling floor screed

The powerful SP 25 DHF auger pump is suitable for conveniently and reliably placing large volumes of self-levelling floor screed. Thanks to the strong three-cylinder diesel engine with 37 kW and “Stage V” emissions, the pump can be operated without issues in the whole of the UK now and in future. The increased efficiency focuses on higher throughputs, longer delivery ranges and higher delivery pressures. The large filling area features a swinging spray guard and a powerful vibrating screen. The low filling height facilitates loading on the construction site as well as the final cleaning. The low pump weight also makes for easier handling on the construction site.



Your benefits

Robust design – tested in construction site use and on the test track

Supports a variety of worm pumps through to the 2L8

Reliable remote control makes possible a variety of functions

Central control with intuitive keypad and clearly arranged display

Larger tank for maximum operational performance without refuelling

Support feet for optimal stability on the construction site

Robust plastic cover according to the highest quality standard for maximum durability SP 25 DHF – robust and powerful, for large volumes of self-levelling floor screed

Safe transfer of machine with crane – thanks to integrated crane lug

Contact the hire desk for further technical information, quotes and availability.

0333 006 5880



The central control panel with intuitive keypad increases operating safety. A clearly structured display behind scratch-resistant protective glass supplies the machine operator with all relevant information.



Conveyor with a volume of 250 l, a larger filling area and a swinging spray guard – with a powerful vibrator as standard. Lower filling height facilitates final cleaning and loading by truck mixer.



The powerful, turbocharged diesel engine with 37 kW and diesel particle filter complies with the requirements of the exhaust emissions standard "Stage V". This means that the pump can be operated in the EU and Switzerland without issues.

Technical Data.

	SP 25 DHF
Feed Hopper	250 l
Pump	Worm pump 7515 Premium
Delivery Rate*	up to 20 m ³ /h
Delivery Pressure	35 bar
Delivery Range**	200 m wide / 60 m high (20 floors)
Tank Capacity	40 l
Engine	3-cylinder Kubota Diesel, 37 kW at 2 700 rpm (Stage V)
Weight	1 050 kg
Length × width × height	4280 × 1410 × 1300 mm
Filling height	730 mm
Maximum particle size	8 mm
Chassis	braked, approved for road use
* The delivery rate is theoretical and depends on the pump pressure.	
** Data are maximum values and depend on material type and consistency, hose diameter and delivery rate.	

Contact the hire desk for further technical information, quotes and availability.

0333 006 5880